



Technical Data



Integrated socket



Tethered



Model NO.		GMR-AC022-EU001
Maximum Power		can be adjusted to : 11kw/16A@400VAC Or 22kw/32A@400VAC
Basic info	Tethered/Socket	Optional
	Connector	Type 2
	Dimension(H*W*D)mm	410*260*164
	Material	Tempered glass front+metal plate back
	Colour	BLACK front + white back or OEM Color
	Indicator	4 LED lights, indicate 4 statuses include power, connect, charging and fault
	Display	4.3-inch



Technical Data

Model NO.		GMR-AC022-EU001
Features	Ethernet(RJ45)	Optional
	RFID	Yes
	WIFI	2.4GHz
	4G	Optional
	RS485	Optional
	OCPP1.6J	Optional
	APP	Optional
	Dynamic Load Balancing	Optional
	Solar charging	Optional
Safety	Ingress protection	IP65, IK10
	Residual current protection	Type A 30mA+ 6mA DC
	Over load protection	Yes
	Over/under voltage protection	Yes
	Short circuit protection	Yes
	Earth leakage protection	Yes
	Ground protection	Yes
	Surge protection	Yes
	Over temperature	Yes
	Certification	CE(LVD, RED) RoHS, REACH
	Certification standard	EN IEC 61851-1, EN IEC 61851-21-2
Environment	Installation	Wall/Pole mounted
	Storage temperature	-40~75°C
	Work temperature	-30~55°C
	Work humidity	≤ 95%RH, No water droplet condensation
	Work altitude	< 2000m
Power Cable	Power Cable Specification	3-phase 4-core 2.5mm ² cable

FLEXIBLE OPTIONS

- Tethered and integrated socket meet different demands.
- Wall-mount or floor stand installation.

SOLID AND RELIABLE

- Special one-piece metal backcover.
- Anti-scraping tempered glass front cover.
- 4.3-inch highlight display.

SAFETY ALWAYS GOES FIRST

- Type A 30mA + 6mA DC leakage protection.
- CE, ROHS, REACH, LVD, RED approved.